

DIVA A70 TECHNICAL SPECIFICATIONS

CONTINUOUS POWER OUTPUT PER CHANNEL

BOTH CHANNELS DRIVEN 8 Ω , 20HZ-20KHZ	50W
SINGLE CHANNEL 4 Ω , 1KHZ	100W
DISTORTION 8 Ω , 80% POWER, 1KHZ	0.005%

PHONO CARTRIDGE INPUT (WHERE FITTED) **MM**

INPUT SENSITIVITY	2.7MV
-------------------	--------------

LINE AND TAPE INPUTS

INPUT SENSITIVITY FOR RATED 8 OHMS POWER OUTPUT	650MV
INPUT IMPEDANCE	22KΩ
SIGNAL TO NOISE RATIO*	98DB

PREAMPLIFIER OUTPUTS

NOMINAL OUTPUT LEVEL	545MV
OUTPUT IMPEDANCE	<50Ω

GENERAL

POWER CONSUMPTION (MAXIMUM)	450VA
SIZE W/D/H MM. INC. FEET	430 x 330 x 85
WEIGHT (NET)	7.5KG

*REF. RATED POWER OUTPUT, 2 VOLTS INPUT, CCIR WEIGHTED, TONE CONTROLS BYPASSED.
ALL UNITS HAVE A FREQUENCY RESPONSE OF 20KHZ-20KHZ +/-0.25DB.

† LINE INPUT SENSITIVITY ON A80/A90 IS USER SELECTABLE +/- 8DB FOR EACH INPUT