

## technical specifications

	SA7K	SA2K	SA1750	SA1730	SA1280	SA1550	SA1530
Power handling	300 Watts	200 Watts	180 Watts	135 Watts	170 Watts	175 Watts	130 Watts
Impedance	4 Ohms	4 Ohms	4 Ohms	4 Ohms	4 Ohms	4 Ohms	4 Ohms
Frequency response	30-35.000 Hz +/- 1.5 dB	40-35.000 Hz +/- 1.5 dB	40-40.000 Hz +/- 3 dB	45-40.000 Hz +/- 3 dB	35-40.000 Hz +/- 3 dB	40-35.000 Hz +/- 3 dB	45-35.000 Hz +/- 3 dB
Sensitivity (1W, 1m)	89 dB	87 dB	90 dB	89 dB	89 dB	90 dB	89 dB
Crossover	600/2800 Hz 24 dB/oct.	3000 Hz 24 dB/oct.	700/3000 Hz 24 dB/oct.	700/3000 Hz 24 dB/oct.	600/2800 Hz 24 dB/oct.	700/3000 Hz 24 dB/oct.	3000 Hz 24 dB/oct.
Dimensions (WxHxD) cm	17.5x136x25	19.5x34.5x30	13x105x28.9	13x95x22.9	15x104x26.6	13x105x27.7	13x95x21.7
Woofer(s)	2 x W7K 4xPDW7K	1xW2K	4xWFP1104AV	2xWFP1108AV	2xW1408AV	4xW1104AV	2xW1108AV
Tweeter	1xTKWG	1xTK	1xTWG2506AV	1xTWG2506AV	1xTWG2506AV	1xTWG2504AV	1xTWG2504AV
Magnetic shielded	no	no	yes	yes	yes	yes	yes
Biwiring	yes	yes	yes	yes	yes	yes	yes
Wall bracket	-	-	-	-	-	-	-
Ceiling bracket	-	-	-	-	-	-	-
Floor stand	-	FS2K	-	-	-	-	-
Built-in amplifier	-	-	-	-	-	-	-
Input voltage	-	-	-	-	-	-	-
Finish (real wood)	Maple Cherry Black Ash	Maple Cherry Black Ash	Maple Cherry Black Ash	Maple Cherry Black Ash	Maple Cherry Black Ash	Maple Cherry Black Ash	Maple Cherry Black Ash
Read page	3	5	6	7	8	10	11