



	SA720 SA720AV	SA710 SA710AV	SA705	SA520 SA520AV	SA510 SA510AV	SA505	SE200	SE175
Power handling	155 Watts	130 Watts	100 Watts	150 Watts	125 Watts	90 Watts	-	-
Impedance	4 Ohms	4 Ohms	8 Ohms	4 Ohms	4 Ohms	8 Ohms	-	-
Frequency response	43-40.000 Hz +/- 3 dB	45-40.000 Hz +/- 3 dB	50-40.000 Hz +/- 3 dB	43-35.000 Hz +/- 3 dB	45-35.000 Hz +/- 3 dB	50-35.000 Hz +/- 3 dB	22-160 Hz +/- 3 dB	30-160 Hz +/- 3 dB
Sensitivity (1W, 1m)	89 dB	89 dB	88 dB	89 dB	89 dB	88 dB	-	-
Crossover	600/3000 Hz 24 dB/oct.	600/3000 Hz 24 dB/oct.	3000 Hz 24 dB/oct.	3000 Hz 24 dB/oct.	3000 Hz 24 dB/oct.	3000 Hz 24 dB/oct.	40-160 Hz 24 dB/oct. var.	40-160 Hz 24 dB/oct. var.
Dimensions (WxHxD) cm	15x42.5x26.4	13x37x26.4	15x28x21.9	15x42.5x25.2	13x37x25.2	15x28x20.7	35x35x35	35x35x35
Woofer(s)	2 x WFP1408AV	2xWFP1108AV	1xWFP1408AV	2xW1408AV	2xW1108AV	1xW1408AV	1xW25	1xW21
Tweeter	1xTWG2506AV	1xTWG2506AV	1xTWG2506AV	1xTWG2504AV	1xTWG2504AV	1xTWG2504AV	-	-
Magnetic shielded	yes	yes	yes	yes	yes	yes	no	no
Biwiring	yes	no	no	yes	no	no	-	-
Wall bracket	WB1	WB1	WB1	WB1	WB1	WB1	-	-
Ceiling bracket	CB1	CB1	CB1	CB1	CB1	CB1	-	-
Floor stand	FS1	FS1	FS1	FS1	FS1	FS1	-	-
Built-in amplifier	-	-	-	-	-	-	380 W impulse	380 W impulse
Input voltage	-	-	-	-	-	-	115 or 230 V	115 or 230 V
Finish (real wood)	Maple Cherry Black Ash	Maple Cherry Black Ash	Maple Cherry Black Ash	Maple Cherry Black Ash	Maple Cherry Black Ash	Maple Cherry Black Ash	Maple Cherry Black Ash	Maple Cherry Black Ash
Read page	13	14	15	16	17	17	18-19	18-19